L Number	Hits	Search Text	DB	Time stamp
2	3974	235/375.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/03/31 18:05
3	950	235/493.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/03/31 18:05
4	653	705/16.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/03/31 18:05
5	212	705/17.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/03/31 18:05
6	3352	((electronic communication system and storage medium).ti.) and 235/$.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/03/31 18:06
7	15	235/$.ccls. and (heat same (reversible or irreversible)) and print$3 and (updat$3 or performance$1)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/03/31 18:06
8	4	4728177.pn. 3978320.pn.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/03/31 18:06
9	116	((707/10.ccls. and attribute) and card) and (magnetic)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/03/31 18:19
10	3675	707/10.ccls.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/03/31 18:19
11	26	((transaction adj card) and(card same (illustration or picture))) and travel	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/03/31 18:19

Web   Images   Groups   News   Froogle^{New!}   more »

Google™

create message system plural tables		**Search**	Advanced Search

Preferences

Web   Results **1 - 10** of about **13,700** for **create message system plural tables**. (0.21 seconds)

package java_cup; import java.util.Enumeration; import java.io. ...
... throws java.lang.Exception { parser parser_obj; /* **create** a parser
and ... Emit a long summary **message** to standard error (**System**.err)
which * summarizes ...
www.cc.gatech.edu/gvu/people/Faculty/hudson/
java_cup/classes.v0.9e/java_cup/Main.java - 29k - Cached -
Similar pages

Sponsored Links

Modular Furniture Systems
Including Panels, Shelves, Drawers,
Work Surfaces, Accessories and more
www.officedepot.com

See your message here...

PostgreSQL 7.4 Documentation (Data Definition)
... Schemas and Privileges 5.8.5. The **System** Catalog Schema ... table before creating
it, ignoring the error **messages**. ... discussed so far you can **create** fully functional ...
www.postgresql.org/docs/7.4/interactive/ddl.html - 17k - Cached - Similar pages

.NET 247 : **Create** class using name? Late bound - HELP! on ...
... I have a persistance manager that will get the row from the appropriate table, **create** a
new Task object (for ... c [Original **message** clipped]. **System**.Data.DataRow. ...
www.dotnet247.com/247reference/msgs/24/121769.aspx - 16k - Cached - Similar pages

SuperMan Pages: n
... newusers, update and **create** new users in batch. shadow-utils. ... ngettext, translate
message and choose **plural** form. ... nhfsstone, Network File **System** benchmark
program. ...
gd.tuwien.ac.at/linuxcommand.org/smp_n.html - 43k - Cached - Similar pages

[PDF] Cray **Message System** Programmer's Guide SG–2121 6.5
File Format: PDF/Adobe Acrobat - View as HTML
Page 1. Cray ® **Message System** Programmer's Guide SG–2121 6.5 Document Number
007–3548–002 Page 2. ... ix Introduction [1] 1 **Message System** Features ... ...
techpubs.sgi.com/library/manuals/3000/ 007-3548-002/pdf/007-3548-002.pdf -
Similar pages

SuperMan Pages: n
... newusers. update and **create** new users in batch. shadow-utils. ... ngettext. translate
message and choose **plural** form. ... nhfsstone. Network File **System** benchmark
program. ...
linuxcommand.org/smp_n.php - 24k - Cached - Similar pages

pro | business AG
... You also should **create** indexes for often used select statements ... would work via the
unique **message** id ... Hugh Darwen [2] An Introduction to Database **Systems** CJ Date ...

www.probusiness.de/projekte/phpgroupware/ sql_style_guide.html - 14k - Cached -
Similar pages

why **tables** rule
... Javascript/DHTML if needs be, but you can **create** most of ... Then again, so would the
windows operating **system**. ... This 64 **message** thread spans 5 pages: ([1] 2 3 4 5 ...
www.webmasterworld.com/forum83/3209-1-15.htm - Similar pages

Lafcadio
... For example, let's say you want to have a simple email-like **system** where users can
send one another **messages**. First, **create** a Messages table in MySQL: ...
lafcadio.rubyforge.org/tutorial.html - 15k - Cached - Similar pages

[Wikitech-I] wiktionary
... 14, brian suda wrote: > this is a **message** based on a ... This database **system** allows
for much more then current free ... It would be easy to **create** a aoftware suited to ...
mail.wikipedia.org/pipermail/wikitech-I/ 2004-February/008376.html - 12k - <u>Cached</u> -
<u>Similar pages</u>

Goooooooooogle ▶

Result Page: **1** <u>2</u> <u>3</u> <u>4</u> <u>5</u> <u>6</u> <u>7</u> <u>8</u> <u>9</u> <u>10</u>   **Next**

| create message system plural tat | Search |

<u>Search within results</u> | <u>Language Tools</u> | <u>Search Tips</u> | <u>Dissatisfied? Help us improve</u>

<u>Google Home</u> - <u>Advertising Programs</u> - <u>Business Solutions</u> - <u>All About Google</u>

©2004 Google